

Data sheets

eco flag 117

Article number: 3745 / 3
Material: 100 % PES
Weight: ca. 117 g/m²

Specialities:

tearproof
transparent
very good print through
heat set for Sublimation
no fraying

Applications:

banners
flags
Beach Flags

Remarks:

Attention: Help for Flag-print-through on the technical data sheet

Very good for DyeSub Direct printers with inline fixation like D.Gen, Aquajet , ATP color

Product compatibilities:

eco flag 117 is compatible to the following printers (print-method):

Vutek FabriVu (Sub Oil)	D-Gen Teleios (Sub water)
Gandi Jeti 3312 DS (Sub Oil)	Vutek QS Series (UV curable)
Durst Rho 160/350/500 (UV curable)	HP Expedio 3200 / 5000 (UV curable)
Paper Transfer (Sub Paper)	Spühl Virtu (UV curable)
Gandi Aquajet (sub water)	ATP Color/Roland (Sub water)

Product attributes:



Data sheets


eco flag 117



Kuhleshütte 84
47809 Krefeld
Germany

Phone: +49 (0)2151 65231-0
Fax: +49 (0)2151 65231-25
Email: info@bergertextil.com
Internet: www.bergertextil.com

Product image:



www.bergertextil.com

++ 49 2151 65231-0

The information in this information sheet are based on findings obtained in practice. Because of the high number of factors which can have an effect during handling and application, customers tests will be required. A legally binding guarantee of specific properties is not to be inferred from our technical information. The information given here may be subject to be changed without notice. Berger has not prepared MSDS datasheets for this product which is not subject to the MSDS requirements.