












DirectTex[®]

Softimage Creaseless Premium[®]

Fields of application

.02 .04 .05 .07

Specifications

	REF. 599221 159
	100 % polyester knit fabrics PVC-free, recyclable
	ca. 160/ 252/ 320/ 505 cm ca. 63/ 99/ 126/ 199 inch other widths available on request
	B-s1, d0 DIN EN 13501-1 M1 NF P 92 503-507 NFPA 701
	ca. 220 g/m ² ca. 6.5 oz/yd ²
	ca. 0.41 mm ca. 410 µm
	rolls 50/ 100 m 55/ 109 yd
	length: 438.7 N cross: 1477.4 N DIN EN ISO 13934-1
	length: 50.7 % cross: 50.6 % DIN EN ISO 13934-1
	blank: 7 DIN EN ISO 105-B02
	length: 1.5 % cross: 0.5 % DIN EN 14704-1
	cold, ultrasonic cut

Printing methods

print	UV	Latex	Dyesub
Inside	•	•	•
Outside			•

Article shrinkage (50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	1,5 %	0,8 %	
190°C	1,7 %	0,9 %	•
200°C	2,2 %	1,0 %	
210°C	3,5 %	1,2 %	

Certifications



DirectTex® Softimage Creaseless Premium

Fields of application

.02 .04 .05 .07



Ref.-Nr.: 599221 159 | Preview print sample