

EMBLEM Walk On Sign II

EMBLEM Walk On Sign II is a structured, white, monomeric soft PVC film for printing with common eco solvent, solvent and latex inks. The foil can be used as floor advertising without laminate. The dot-like structures on the surface provide the slip-resistant effect.

Matchcode: WOS2

Material: soft PVC film, monomeric

Finish: structured with outstanding dots

Color: white

Thickness: $100 \,\mu \text{m}$ basic film

Adhesive: transparent, semi permanent acrylate adhesive

Liner: siliconised kraft paper, 120 g/m²

Adhesion: 5 N/25 mm - 24 h AFERA 5001 (average value)

Adhesive weight: 20 g/m²

Dimensional stability: length: < -2 % - cross: < 0 %, acc. FINAT TM 14

Application temperature: more than 8 °C

Fire behaviour: not easily flammable - B1 – acc. DIN 4102-14 on mineral

substrate

Anti-Slip property: R 9 acc. DIN 51130

Standard rolls width: 1370 mm Standard roll length: 25 m

Storage: cool and dry environment, at 15-25 °C, 50 % rel. humidity

Shelf life: 24 month in original packing

COMPATIBLE INKS:

Eco Solvent: yes UVC: yes Solvent: yes Latex: yes

Different printers, inks, resolutions and printing qualities result into numerous different printing parameters. In addition, there a numerous factors influencing processing and the application of our materials. For this reason, we cannot make specific statements as to drying times and maximum ink absorption. For this reason, we recommend you to perform own tests in order to verify the desired results. Our product specifications are not to be understood as legally binding guarantees assuring specific characteristics. Any liabilities and guarantees, as well as claims for compensation beyond the value of the product itself are excluded.





EMBLEM Walk On Sign II

Description:

Floor advertising with EMBLEM Walk On Sign II gets the full attention of the visitors by colour-intensive prints. A fast and cost-efficient production can be realized with the Walk On Sign II, because a lamination after printing is not necessary. The semi-permanent adhesive allows a good repositioning when applying the film and an easy removal at the end of the advertising campaign.

The vinyl complies with fire protection class B1 according to DIN 4102-14 for floor coverings. In addition, the Walk On Sign II is slip-resistant certified according to DIN 51130. In the test, the rating class R9 was achieved. The product can therefore be used as floor advertising in shopping centres and supermarkets, depending on local specifications. The advertising message can be used indoors for up to 3 months - depending on the degree of stress.

The product is REACH and RoHS compliant.

Processing:

The vinyl can be removed easily from many smooth and firm substrates after short term use. Apply the film on flat surfaces. The subsurfaces to be pasted up with the vinyl have to be free of dirt, dust and grease. We advise to check compatibility between adhesive and subsurface - please test before application.

After printing it is necessary to wait for an outright drying and fumigation of the print to avoid diffusion of solvents.

To avoid fingerprints the use of cotton gloves is advised.

Application:

Typical applications are floor advertising on smooth surfaces in inner areas, such shopping centres, supermarkets, entrance areas, railway stations, airports, ...