

## frontlit light eco (H5022-0295)



**Base fabric** (DIN ISO 2076)  
*Trärgewebe*

100% Polyester




**Total weight** (DIN EN ISO 2286-2)  
*Flächengewicht*

ca. 500 g/m<sup>2</sup> | 15 oz/yd<sup>2</sup>



**Coating material**  
*Beschichtungsmaterial*

PVC



**Tensile strength** (DIN EN ISO 1421-1)  
*Höchstzugkraft*

2800/2100 N/5 cm | 320/240 lbs/inch



**Production width**  
*Produktionsbreite*

320/500 cm | 126/197inch



**Tear strength** (DIN 53363)  
*Weiterreißkraft*

ca 410/310 N | approx. 92/70 lbs



**Storage stability**  
*Lagerstabilität*

6 months in temperate zones  
*6 Monate in gem. Klimazonen*



**Flame retardancy** (DIN 75200)  
*Schwer entflammbar*

max. 100 mm/min | 3.9 inch/min

For possible errors no liability will be assumed. Subject to alterations without prior notice; errors including printer's errors. The product is subject to fluctuations.

Für eventuelle Fehler wird keine Haftung übernommen. Druckfehler und Irrtümer vorbehalten. Änderungen können jederzeit ohne vorherige Ankündigung vorgenommen werden. Das Produkt unterliegt Schwankungen.

Status: 2016.10.26