

Technical Data Sheet

updated
checked

19.11.2015
19.11.2015

Product

6548K
with special heat setting and make-up
for digital printing

Material

100 % Polyester

Stock widths

app. 320 cm

Possible widths

app. 160cm, 253cm, 320cm

Finishing

rolled on paper cores

Packaging

wrapped with foil

Ecology

according to Öko-Tex Standard 100,
product class II

Tinte

transfer printing,
direct printing with dye-sub inks,
direct printing with UV curing inks,
direct printing with HP Latex inks

Weight

acc. to DIN EN 12127 110.00 [g/m²] +- 3 [&]

Tearing strength

Maximum tensile elongation, longitudinal
direction

acc. to DIN EN ISO 13934-1 70.00 [%] +- 20 [%]

Maximum tensile elongation, cross direction

acc. to DIN EN ISO 13934-1 30.00 [%] +- 20 [%]

Maximum tearing strength, longitudinal
direction

acc. to DIN EN ISO 13934-1 min. 220.00 [N/5 cm]

Maximum tearing strength, cross direction

acc. to DIN EN ISO 13934-1 min. 680.00 [N/5 cm]

We do not accept liability for errors. Printing mistakes and changes are reserved.

Please pay attention to our general considerations regarding fabrication at www.g-o-friedrich.com