

MasterJet S Dot Fix Premium

Highlights

- Bubble-free & easy to apply
- residue free removable dot adhesive



	Technical specifications
Material	Monomeric soft PVC film
Colour	White and transparent, matt and glossy respectively
Area of application	For short to medium-term indoor applications such as temporary advertising spaces at the POS or in shopping centres, short-term trade fair and event signage, shop window decorations and promotional stickers. For simple, bubble-free bonding. Not suitable for non-polar substrates.
Masking material	PE-coated silicone paper, 140 g/m ² , white
Pressure-sensitive adhesive	Polyacrylate, removable, transparent, repositionable
Adhesive strength (AFERA 4001, 10 min.)	>1 N/25 mm
Thickness (without protective paper and adhesive)	100 µm ±10
Bonding temperature	+18 °C to +25 °C
Application temperature	-30 °C to +50 °C
Printing process	Inkjet printing with solvent-based inks, UV or latex inks. When printing with UV printers with intensive UV radiation, premature ageing (embrittlement) of the transparent films may occur. We recommend carrying out your own tests.
Certificates	Fire behaviour certified according to EN 13501-1
Shelf life (in original packaging, at 18-25 °C and 40-65 % relative humidity)	12 months
Processing instructions	The print should dry completely before the material is further processed or laminated. At least 24 hours drying time is recommended for solvent printing. The material should be stored loosely rolled up to allow air circulation. The surface to be bonded should be clean, dry and free of dust, grease or silicone residue - this ensures optimum adhesion of the film. Wet application is not recommended. The films can usually be easily removed from most surfaces without leaving any residue. However, adhesive residues can occur on PVC substrates. In the case of very hot surfaces (e.g. shop windows, metal), it is recommended that the material is allowed to cool before removal to facilitate clean removal. Adhesive residues (if present) can be removed with methylated spirits. Vertical storage in the original carton is recommended.
Characterisation according to REACH regulation	The product is an article according to Regulation (EC) No 1907/2006 Article 3 (REACH Regulation).

MasterJet S Dot Fix Premium

SVHC / REACH	Based on the supplier declarations available to us, we can confirm that this product does not contain any of the substances in a concentration of more than 0.1% by weight that are included in the list of Substances of Very High Concern (SVHC) for authorisation issued by the European Chemicals Agency (ECHA) (https://echa.europa.eu/de/candidate-list-table).
Dimensions	137.0 cm x 50 m (SFI-MDFPWGR137-50) 105.0 cm x 50 m (SFI-MDFPWMR105-50) 137.0 cm x 50 m (SFI-MDFPWMR137-50) 160.0 cm x 50 m (SFI-MDFPWMR160-50) 105.0 cm x 50 m (SFI-MDFPTGR105-50) 137.0 cm x 50 m (SFI-MDFPTGR137-50) 160.0 cm x 50 m (SFI-MDFPTGR160-50) 137.0 cm x 50 m (SFI-MDFPTMR137-50)

This information corresponds to the current state of our knowledge and is intended to provide non-binding information about the products and their possible applications. A legally binding assurance of certain properties cannot be derived from our information. All information without guarantee. Status 07|2025