

Stafix® STATIC is a glue- and PVC-free self-adhesive material that adheres to various clean and smooth surfaces with static charge.

STAFIX
STATIC

Version 2024-1

Stafix® STATIC
Product datasheet

- For short and mid-term usage
- Lifespan average 3 months
- Ideal for sensitive surfaces
- Extremely easy to install and remove
- Glue and residue-free, reusable, recyclable

Formats and printing compatibility

Material for printing test available upon request.

PRODUCT	PRINTING	APPEARANCE	SHEETS	REELS
Offset	Oxidative, UV and UV-LED Offset	White and clear	320 x 450 480 x 650 707 x 1000	
Indigo	HP® Indigo	White and clear	320 x 460 530 x 750	
UV-Inkjet	UV-Inkjet, UV-Led	White and clear		700 mm x 50 m 700 mm x 100 m

Recommended applications

- Perfect for short and mid-term ads, promotions, and decorations with quick turnover.
- Suitable for sensitive surfaces like TV screens and white-label products, and ideal for retail ads in beverages, frozen food, ice creams, pharmaceuticals, and seasonal promotions.



Offset and Indigo product data



OFFSET					INDIGO			
	White		Clear		White		Clear	
	Film	Backer	Film	Backer	Film	Backer	Film	Backer
Weight (g/m ²)	36.3	180	45.5	180	36.3	220	45.5	220
Thickness (mm)	0.050	0.260	0.050	0.260	0.050	0.230	0.050	0.230
Total Weight (g/m ²)	216.3		225.5		256.3		265.5	
Total Thickness (mm)	0.310		0.310		0.280		0.280	
Film	PP		PP		PP		PP	
Backer	180 g cardboard				220 g cardboard			

UV-Inkjet product data



UV-INKJET					
MATERIAL		White		Clear	
	Film	Backer		Film	Backer
Weight (g/m2)	36.3	200		45.5	200
Thickness (mm)	0.050	0.152		0.050	0.152
Total Weight (g/m2)	216.3			225.5	
Total Thickness (mm)	0.310			0.310	
REELS					
Reel Length (m)	50	100		50	100
Reel Width (mm)	700			700	
Reel Diameter (cm)	15	19.5		15	19.5
Core (mm)	7.62 (3")			7.62 (3")	
Reel Weight (kg)	9.8	18.2		10.1	18.8
Film	PP			PP	
Backer	180 g cardboard			180 g cardboard	

NOTE! Printing on Static film is not the same as printing on plastic. Carefully follow the printing guidelines to avoid potential problems. Read more at www.stafix.eu

Important: All information concerning Stafix® products is based on current quality levels. Stafix Ltd. reserves the right to change the specifications of the contents as part of our continual product development. Before using the material, the end user must analyze the suitability of the material for the specific application. Stafix Ltd. does not assume liability for the unsuitable performance of the material.

Stafix Ltd
Kontisentie 8B
40800 Vaajakoski
Finland
info@stafix.fi
www.stafix.eu
VAT: FI20849407

Recyclability:

PP: Grade 5 plastic
Backer: Paper

Shelf life:

12 months, following storage guidelines

Usage:

Before applying the material, the surface must be clean, dry and grease-free.